


CHALLENGE 300-HT

Synthetic Grinding Fluid for Glass & Ceramic



Description

CHALLENGE 300-HT is a synthetic formulation developed to optimize removal rate and surface finish in grinding, sawing and dicing processes using diamond grinding wheels and blades. The product's exceptional heat transfer characteristics insure prolonged diamond life, even with the most difficult materials.

CHALLENGE 300-HT is compatible with all filtration systems, and its foam-free operation promotes operator acceptance.

Benefits

- ⇒ Biodegradable
- ⇒ Non-staining
- ⇒ Better surface finishes
- ⇒ Compatible with all filtration systems
- ⇒ Faster removal rates
- ⇒ Non-corrosive
- ⇒ No foam
- ⇒ Operator acceptance
- ⇒ Extended diamond life

Directions

CHALLENGE 300-HT is designed for use at economical dilution ratios, is equally effective in hard/soft water and suitable for "recirculating systems" mainly.

For optimum results, follow the dilution ratios listed below, making production specific adjustments as needed:

- | | |
|---------------------|-----------|
| ⇒ Surface/Blanchard | = 30-50:1 |
| ⇒ O.D./Cylindrical | = 30-50:1 |
| ⇒ Edge/Bevel/Dicing | = 50-75:1 |

Maintaining dilution ratios with a hand-held refractometer is recommended. A pH meter is also useful. Develop production-specific scales by obtaining accurately measured samples of a properly diluted mixture that corresponds to use. Maintain a higher concentration for recirculating, filtered coolant systems

Additional Information

CHALLENGE products are available in 5-gallon pails and 55-gallon drums, F.O.B. Bethel, Connecticut, and also include: sawing fluids, suspension additives for lapping/polishing slurries, rinse/wet storage additives and ultrasonic/megasonic detergents. Material Safety Data Sheets available upon request.

Manufacturer: **INTERSURFACE DYNAMICS, Inc.**
 Supplier: **N. BUCHER AG**, Pfadackerstrasse 9, 8957 Spreitenbach/Switzerland
 Phone: ++41-56 418 19 90
 Fax: ++41-56 418 19 99
<mailto:info@nbucheraq.com>